



Professional mobile dehumidifier

MOBILE DEHUMIDIFIER FOR DRYING IN INDUSTRIAL SITES AND IN CASE OF WATER DAMAGES FD 65



Easy to clean

FD 65 is the most representative dehumidifier of the new generation.

It is equipped with a drain pump with 5 meters of reinforced hose, no need to empty the water tank or raise the unit, there will always be a window or a sewer scope around.

Its many built-in features and its capacity of 65 L / day make of it the ideal machine for rental. It can be adapted to all situations. FD 65 can satisfy the most demanding customers.

Its rotomolded plastic body is ultra strong and regains its shape on impact.

With a width of 51cm and a weight of 37kg, the FD 65 is a device that can be loaded and unloaded in a vehicle by a single man, then transported easily on the disaster site. The semi-pneumatic wheels and the telescopic handle request limited efforts.

For permanent use of the dehumidifier in industry or food industry.

The FD 65 is fitted with a humidity display and an electronic room control.

Thanks to its active defrost by hot gases, the FD 65 can even be active in none heated ambiances close to 0°C.

Many other benefits for professionals:

- Automatic restart in case of current shut off
- Washable dust filter available in front of unit
- Delayed start to protect the unit after transport
- 12 hours Timer
- Limited maintenance

Technical data

Dehumidification : 30°C/80% RH	65 liters per day
Dehumidification : 27°C/60% RH	38 liters per day
Electric power	750 W
Intensity	3,3 A
Power	230 V (Ph+N) - 50Hz
Airflow	400 m ³ /h
Refrigerant	R410A, 560g
Relative humidity display	Yes, on 2 digits
Condensate drain diameter	12 mm with a 5m reinforced hose supplied
Width / Depth / Height (machine)	510mm / 485mm / 810mm
Width / Depth / Height (packaging)	560mm / 540mm / 580mm
Weight	37 kg
Operating temperature range	1 - 32°C
Operating humidity range	40 - 100 % RH
CE / TÜV / RoHS	Yes